



PG 16804/4248



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 22 OCT 2004

WIPO

PCT


PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

[Signature]


Dated

18 October 2004

BEST AVAILABLE COPY

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

2. Patent application number

(The Patent Office will fill in this part)

0323848.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

BAE SYSTEMS plc

6 Carlton Gardens
London, SW1Y 5AD

Patents ADP number (*if you know it*)

07914674004 ✓

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

DESIGN BY SPACE TRANSFORMATION
FROM HIGH TO LOW DIMENSIONS

5. Name of your agent (*if you have one*)

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

BAE SYSTEMS plc
Group IP Department
Lancaster House, P.O. Box 87
Farnborough Aerospace Centre
Farnborough, Hampshire, GU14 6YU

Patents ADP number (*if you know it*)

07914674002 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)

Date of filing
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 24

Claim(s) 02

Abstract 01

Drawing(s) 19 a 19

3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Aniruddha Mukherjee

Date

Aniruddha Mukherjee

10/10/2003

12. Name and daytime telephone number of person to contact in the United Kingdom Maria Burkes 01252 383487

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

- 1 -

DESIGN BY SPACE TRANSFORMATION FROM HIGH TO LOW DIMENSIONS

Field of the Invention

This invention concerns design by space transformation from high to low dimensions. More particularly but not exclusively, this invention concerns methods and systems for design by transforming data from a high to low dimensional design space.

Background of the Invention

There are considerable cost benefits to be derived from improving designs both by better searches in current design spaces and by satisfying more complex design criteria, for instance by striking the right balance between multiple objectives from the same discipline or from different disciplines.

In known design processes designers typically spend a prohibitively long time preparing individual analysis cases and, are constrained to sampling small areas of the design space close to previously explored regions. In such a design processes, complex design tasks are broken down into manageable portions so that specialists in individual disciplines can resolve different parts of the design. However, such portions are too small and there is too much iteration between disciplines which prohibits the challenging of the constraints of one discipline by another, where the most progress is likely to be made. Furthermore, known design space exploration techniques as applied to complex multi-dimensional design spaces are invariably inefficient on account of the associated high computational processing cost required for the data analysis. Also, such techniques can be problematic to use in complex multi-dimensional design spaces because these typically rely on simplistic data analysis models involving different parameters - for example, numerical errors or uncertainties associated with discretisation, incomplete convergence, irregular constraint boundaries can arise. The inventors have recognised that this situation can be ameliorated if small numbers of individuals can assimilate, appreciate and understand large amounts of data rapidly and efficiently. With this in mind, this inventive work is aimed directly at the designers in the design process of the future, who communicate with and steer the design search and optimisation process and who

can extract previous work from databases transparently and flexibly. They can use software and data as web services, so that the source of this data and software becomes unknown and unimportant. Such designers make use of high cost analysis codes within automated search and response surface models to map and optimise domains using computationally expensive evaluations. They can use low fidelity (or computationally inexpensive) models to navigate high fidelity design spaces. The placement of analyses in the design space are defined by design of experiments (DoE) methods both as schemes defined *a priori* and as a result of optimisation or error-defining processes. These engineers, armed with more information and understanding, can be expected to regularly challenge cross-discipline constraints. They are more concerned with problem definition, design space shape and optimisation than how any one analysis is obtained and use advanced visualisation techniques to provide enhanced comprehension and effective navigation of hyper-dimensional design spaces.

Objects and Summary of the Invention

The present invention aims to overcome or at least substantially reduce some of the above mentioned drawbacks associated with known processes.

It is an object of the present invention to provide a method and system which are reliable for providing enhanced comprehension and effective navigation of multi-dimensional design spaces.

In broad terms, the present invention resides in the concept of transforming data from a high-dimensional to low-dimensional design space and, by inspecting the transformed data in the low-dimensional design space, enabling an optimum value for a functional representation of the transformed data to be established, and thereby permitting effective exploration of the high-dimensional design space.

According to a first aspect of the present invention there is provided a method of transforming data from a high-dimensional to low-dimensional design space and deriving an optimum value for a predetermined function representative of the transformed data in the low-dimensional design space, which derivation is

further effected in the low-dimensional design space in dependence upon an inspection of the transformed data.

According to a second aspect of the present invention there is provided a method of transforming data from a high-dimensional to low-dimensional design space, and deriving a conditional value for a predetermined function representative of the transformed data in the low-dimensional design space, which derivation is further effected in the low-dimensional design space in dependence upon an inspection of the transformed data.

It is to be understood here that the terms "optimum value" and "conditional value" herein are interchangeably used insofar as they are intended to correspond to the highest or lowest value of the functional representation of the transformed data in the low-dimensional design space, the particular various constraints to the design space problem being further satisfied at the same time.

In accordance with an exemplary embodiment of the invention which will be described hereafter in detail, the optimum/conditional value is derived by (a) establishing a mathematical combination of a number of independent design variables and dependent design variables relating to the function, and (b) modifying the combination in the low-dimensional design space to derive therefrom the desired value for the function at which various constraints associated with the function are satisfied and at which the function has a conditional high or low value in relation to other possible values of the function which are determined in accordance with the modification of said combination.

Conveniently, the transformation into the low-dimensional design space is performed by application of a Generative Topographic Map (GTM) technique. It is to be appreciated that alternative transformation techniques, the self-organizing map (SOM) after Kohonen [13], for example, could be used instead for this particular application.

In accordance with another embodiment of the invention which will be described hereinafter in detail, the method comprises the step of transforming data from a first high-dimensional design space and from a second, different high-dimensional design space into a low-dimensional design space, comparing

the different transformed data sets in said low-dimensional design space and identifying therefrom similarities between the different transformed data sets to indicate a correspondence between the first and second high-dimensional design spaces. This provides an effective way of assessing the importance and inter
5 relationship of design variables in different high-dimensional design space problems. In this embodiment, to be described hereafter, the first high-dimensional design space is a 5-dimensional design space, the second high-dimensional design space is an 8-dimensional design space, the third high-dimensional design space is a 14-dimensional design space, and the low-
10 dimensional design is a two-dimensional design space. It is to be appreciated, however, that various other kinds of high-dimensionality design space can be readily accommodated, if desired.

Advantageously, the data transformation into the low-dimensional design space is performed in a manner which takes account of the effect of each of the
15 design variables relating to the function. This makes optional the need for any pre-screening of the design variables.

Optionally, the optimum/conditional value derivation is effected by generating an image map representation of the transformed data in the low-dimensional design space (for example, a 2-D image map representation may be
20 generated), and visually identifying an intersecting region in the image map representation, which intersecting region provides an indication of said value. It is to be understood that the identification step could be performed computationally, if desired, so as to provide the required technical effect.

The invention has utility for aircraft design applications and although this
25 technology has been developed with reference to aircraft aerodynamic design in particular, the design space visualization and curve fitting technology developed is general. It should therefore be equally applicable to other disciplines such as cost analysis, structures and computational electromagnetics, in which expensive analysis tools are used to find optima for complicated design problems. It is
30 expected to be particularly useful in multi-disciplinary design and situations where there are multiple optima in the design space.

It is to be appreciated that the present invention may be embodied in software. Accordingly, the present invention extends to a computer program element comprising program code for configuring a programmable device apparatus or system to implement the above described method. Suitably, the computer
5 program is stored on a carrier medium.

Further, the present invention extends to a data processing system or apparatus for transforming data from a high-dimensional to low-dimensional design space adapted and arranged to implement the above described method.

The above and further features of the invention are set forth with
10 particularity in the appended claims and will be described hereinafter with reference to the accompanying drawings.

Brief Description of the Drawings

Figure 1 shows a schematic representation of an RSM-Based Design
Process;

15 Figure 2 shows an image representative of a design space for an analytical function;

Figure 3 shows a series of conventional scatter plots;

Figure 4 shows a set of self-organising maps for a 2-D analytical problem;

Figure 5 shows an alternative image representation of the image of Figure
20 2;

Figure 6 shows the typical result of transforming the image representation of Figure 5 into a triangle;

Figure 7 shows the typical result of transforming the image representation of Figure 5 into an SOM;

25 Figure 8 shows the typical result of transforming the image representation of Figure 5 into a GTM;

Figure 9 shows the typical result of a 50 x 50 evaluation of a 2-D design space using a 2-D panel method;

Figure 10 shows a series of scatter plots for a 5-D military aircraft problem;

Figure 11 shows a set of self-organising maps for a 5-D military aircraft problem;

Figure 12 shows a 5-dimensional Hierarchical Axes Technique plot;

Table 1 shows a typical set of results for design space optimisation as
5 obtained from the Kriging Process;

Table 2 shows a set of results corresponding to Figure 13 for design space optimisation, as obtained from GTM optimisation for a 5-D problem;

Figure 13 shows an image map representation of transformed data in 2-D design space, in accordance with an embodiment of the invention;

10 Figure 14 shows a loading distribution plot of optimised wing design corresponding to an inventive application of an embodiment of the present invention;

Figure 15 shows an image map representation of transformed data in 2-D design space, as obtained from GTM transformation of an 8-D aerodynamic
15 problem;

Figure 16 shows another image map representation of transformed data in 2-D design space, as obtained from GTM transformation of a 14D aerodynamic problem; and

Figure 17 shows how points on a regular grid in low-dimensional space
20 are mapped using a non-linear mapping to corresponding centres of Gaussians.

Detailed Description of Exemplary Embodiments

This invention is to be described in the following way. The application of visualisation and design space transformation on a two-dimensional analytical problem is described and then extended for use in military
25 aircraft design. A two dimensional visualisation of a representative military aircraft problem is described and then extended to 5, 8 and 14 dimensions. The description includes a specification of the optimisation problems and a *modus operandi* for a design process is introduced. The visualisation is compared to alternative techniques, such as scatter plots and SOM visualisations. Possible
30 applications of the different visualisation methods, in conjunction with response

surface method technology, are also described. The proposed inventive process whereby the transformed design space is then used to obtain the optimum in the design space is explained. The proposed process and usual process are compared for the 5-D problem. It is shown how by implementing the proposed process the solving and understanding of multi-dimensional design spaces can be effectively performed in a two-dimensional image.

Modus Operandi

It is to be appreciated that the large amounts of data required for design space appreciation can be provided by response surface method technology. Visualisation is part of a *modus operandi*, as shown in Figure 1. This comprises first, a problem specification, in terms of objectives, constraints and design variables. Then a DoE (e.g. Latin Hypercube [3], LP, [4]) is performed and a response surface methodology applied (for instance kriging, radial basis functions [5,6,7], etc.). An update strategy is then determined by statistical methods, such as expected improvement or the optimum in the domain based on the visual inspection of maps. As part of this process an assessment takes place as to the importance of the design variables in the problem. The inventors have found that the first visualisation method proposed ceases to work after about 6 dimensions. The inventors propose to transform the spaces described from high dimensions (5, 8 or 14-D in this case) to just two or four dimensions by use of the generative topographic map (GTM) (although the exact dimensionality of the low dimensional transform is optional).

As previously mentioned, the invention is described hereinafter by use of two example problems. First, a simple two-dimensional analytical problem, from Schwefel's book [1] as described. Secondly, a military aircraft optimisation in 2, 5, 8 and 14 dimensions is described. More conventional design space appreciation and response surface fitting methodology is also described.

Analytical Problem Specification

A two-dimensional analytical function is chosen so that full appreciation of the design space and comparison with the transformations is possible. It is

assumed that if transformations are poor in two-dimensions then their application in higher dimensions will be even worse.

The analytical problem is shown in Figure 2 where the objective function (Ob) and the constraints (C_1 to C_7) are defined as:

$$\begin{aligned}
 Ob(x) &= -x_1^2 - x_2^2 \\
 C_1(x) &= -x_1 \\
 C_2(x) &= -x_2 \\
 C_3(x) &= -x_1^2 - x_2^2 + 17.0x_1 + 5.0x_2 - 66.0 \\
 C_4(x) &= -x_1^2 - x_2^2 + 10.0x_1 + 10.0x_2 - 41.0 \\
 C_5(x) &= -x_1^2 - x_2^2 + 4.0x_1 + 14.0x_2 - 45.0 \\
 C_6(x) &= x_1 - 7.0 \\
 C_7(x) &= x_2 - 7.0
 \end{aligned}$$

In this definition, a constraint is considered satisfied if it is ≤ 0.0 . The objective function is not drawn in the domain where any of the constraints are violated. The traces show all the evaluations made using an SQP optimisation method from multiple starts along the line $x_1 = 3.0$. The SQP method used was by Madsen [1] and based on the Harwell Library Subroutine VE02AD. Alternative starts, for example along the $x_1 = 0.0$ line also find the optimum at [0.5]. The problem lies in being able to extend plots like this to multiple dimensions.

The results achieved for this optimisation depend on which constraints are active when the problem is solved. The four possible local minima occur where the constraint boundaries intersect:

- $x = (0, 5)$, $Ob(x) = -25$, constraints 1 and 5 active;
- $x = (2.116, 4.174)$, $Ob(x) \approx -21.90$, constraints 4 and 5 active;
- $x = (5, 2)$, $Ob(x) = -29$, constraints 3 and 4 active;
- and $x = (6, 0)$, $Ob(x) = -36$, constraints 2 and 3 active.

The global optimum, the optimum of all the local optima, is at $x = (6, 0)$, $Ob(x) = -36$, with constraints 2 and 3 active

A good SQP algorithm would be one which would find all the local optima at intersections of the constraint boundaries and then the designer would inspect these and find the best answer from them. At this point he may also wish to take additional considerations into account.

Additional plots can be used to further interrogate the data. First, a series of scatter plots can be drawn as shown in Figure 3, in which every item of data can be plotted against every other item of data that is, of every dependent and independent variable of interest against every other variable. Scatter plots are widely used by the statistics community, see for example [10]. These plots enable a good appreciation of the design space and to establish whether or not known trends are being followed. This process confirms for instance the nature of the design of experiments (DoE). Here, design variable 1 and design variable 2 are chosen at every corner point of a mesh, which subdivides the design space equally. The quadratic nature of the constraints is also discernible. Alternatives to this include parallel co-ordinates [11, 12] or SOM's). These latter methods also enable relationships between variables to be obtained [14] and, possibly, to establish the most important variables in the problem.

Figure 4 shows a set of SOM's for this data. The directions of x_1 and x_2 are horizontal and vertical respectively, showing that they are orthogonal in the design space. The objective ($-x_1^2 - x_2^2$) is monotonically related to c_2 as the diagonal lines go in the same directions and the colour changes from bottom left to top right. x_1 and c_1 are shown to be inversely related as the colours are in the opposite directions, but still horizontal in both maps. Similarly c_3 is inversely related to x_2 . The functions c_1 , c_2 , c_3 and the objective are all circular. (See U.K. patent application No. 0228751.4).

Although the SOM appears to be able to detect relationships between functions it does not facilitate the scrutiny of play off between domain constraints. In addition the location of function minima is also desirable, along with tracking the paths of optimisations. These properties can all be identified, for a 2-dimensional problem in Figure 2. An alternative representation of Figure 2 is shown in Figure 5. Note that in the Figure the feasible region is denoted by the white circles and the infeasible by the black circles. The full extent of the constraints is also shown. Thus, the complete domain is shaded and the feasible and infeasible regions are determined by the colour of the circles. The circles represent the DoE and are drawn for every other point in the design space. The

complete extent of the constraints is shown. This representation follows the annotation of Grossman et al [16], in which a 28 dimensional space is represented as a triangle. The triangle in [16] is a mapping of 28 dimensional vectors into 2-D, 3 points are chosen to form the corners of the triangle. These
5 may be local optima or perhaps two local optima and one intermediate point. All the intermediate points are then obtained as being a certain distance away from these reference points. The actual objective and constraints are then plotted as usual in a 2-D plot. A fourth reference point would then be required to turn the 2-D representation into a solid object. This technique necessarily incurs a loss in
10 data structure, and a triangle is a relatively complicated mapping, particularly in higher dimensions. To understand the limitations of this method this mapping is presented for the circular function in Figure 6 and can be compared directly with Figure 5, except that the extent of the colour map is reduced in the triangular representation. Additional points outside the triangle could also be obtained by
15 extrapolation. Note that in Figure 6 the optima at $x=[6,0]$, $x=[5,2]$ and $x=[2.116,4.174]$ form the corners. Intermediate points are obtained by interpolation. Although this transformation could provide some appreciation of a high dimensional space the problem with it is that the space extent is unknown. As such it can be used to appreciate space around known points in the domain,
20 but whether all the optima are captured or the required amount of space has been visualized is not known.

A transform is required which has a better 2-D manifold. The SOM is a projection and visualisation of a high-dimensional signal space on a two-dimensional display. Therefore it should be possible to use the SOM rather than
25 a triangle for the 2-D manifold. Returning to the SOM it is clear that the tessellated hexagons used previously are relatively coarse. In fact, a much finer, rectangular definition is possible. The equivalent SOM to Figure 5 is next shown in Figure 7. However, the SOM is found not to give very good results and the mapping from topographic space to the data space is only defined at the location
30 of the nodes.

The Generative Topological Mapping (GTM) is intended as an alternative computation of the SOM, in an attempt to define the metric relations between the

models on the map grid with improved fidelity to those in the data space. The trade-off is a higher computational cost. The equivalent GTM to Figure 5 is shown in Figure 8. The orientation of these maps is always somewhat arbitrary, so rotation through 90 degrees anticlockwise shows a very similar representation compared to Figure 5. This transformation will now be applied to a military aircraft design problem.

Military Aircraft Design Problem Specification

The problem is to minimise the drag coefficient (C_D) of a representative Military Aircraft trapezoidal body/wing tail-less aircraft in cruise at $M=0.85$, subject to:

5-D Problem:

$$\begin{aligned}
 &-3.0 \leq \text{wing linear twist (washout, } \theta) \leq 7.0 \\
 &-3.0 \leq \text{wing angle of attack } (\alpha) \leq 7.0 \\
 &0.0 \leq \text{mid-camber} \leq 0.07 \\
 &0.0 \leq \text{flap deflection angle } (\delta) \leq 10.0 \\
 &9.557 \leq \text{leading edge (l.e.) tip location} \leq 14.227 \\
 &C_L \geq 0.1994 \\
 &C_{m_{total}} = C_{m_{le}} + hC_L \cos \alpha + hC_D \sin \alpha \\
 &\Rightarrow c_1 = \frac{C_L + a_3}{-\frac{C_{m_{le}}}{h \cos \alpha} - C_D \tan \alpha + a_3} = 1.0
 \end{aligned}$$

8-D Problem:

$$\begin{aligned}
 &-0.01 \leq \text{Root Camber at } 30\% \bar{c} \leq 0.025 \\
 &-0.01 \leq \text{Root Camber at } 60\% \bar{c} \leq 0.04 \\
 &-0.01 \leq 50\% \text{ Semi-span Camber at } 30\% \bar{c} \leq 0.025 \\
 &-0.01 \leq 50\% \text{ Semi-span Camber at } 60\% \bar{c} \leq 0.04 \\
 &-0.01 \leq \text{Tip Camber at } 30\% \bar{c} \leq 0.025 \\
 &-0.01 \leq \text{Tip Camber at } 60\% \bar{c} \leq 0.04
 \end{aligned}$$

15

$$\begin{aligned}
 &0^\circ \leq \alpha \leq 7^\circ \\
 &-3^\circ \leq \theta \leq 3^\circ \\
 &\text{subject to the constraints:} \\
 &C_L > 0.1994 \text{ and } |C_m| < 0.02
 \end{aligned}$$

14-D Problem:

$-0.01 \leq \text{Centre line Camber at } 20\% \bar{c} \leq 0.02$
 $-0.01 \leq \text{Centre line Camber at } 40\% \bar{c} \leq 0.03$
 $-0.01 \leq \text{Centre line Camber at } 70\% \bar{c} \leq 0.03$
 $-0.01 \leq 40\% \text{ semi-span Camber at } 20\% \bar{c} \leq 0.02$
 $-0.01 \leq 40\% \text{ semi-span Camber at } 40\% \bar{c} \leq 0.03$
 $-0.01 \leq 40\% \text{ semi-span Camber at } 70\% \bar{c} \leq 0.03$
 $-0.01 \leq 70\% \text{ semi-span Camber at } 20\% \bar{c} \leq 0.02$
 $-0.01 \leq 70\% \text{ semi-span Camber at } 40\% \bar{c} \leq 0.03$
 $-0.01 \leq 70\% \text{ semi-span Camber at } 70\% \bar{c} \leq 0.03$
 $-0.01 \leq \text{Tip Camber at } 30\% \bar{c} \leq 0.02$
 $-0.01 \leq \text{Tip Camber at } 50\% \bar{c} \leq 0.03$
 $-0.01 \leq \text{Tip Camber at } 60\% \bar{c} \leq 0.03$
 $1^\circ \leq \alpha \leq 7^\circ$
 $-3^\circ \leq \theta \leq 3^\circ$
 subject to the constraints:
 $C_L > 0.1994$ and $|C_m| < 0.02$

where C_L is the lift coefficient and C_m the pitching moment coefficient.

- 5 CFD evaluations are performed using the BAE SYSTEMS in-house code FLITE3D [8] in inviscid, Euler mode.

Visualisation

- Figure 9 shows a visualisation of a related two-dimensional design space, with computational noise and failed evaluations. (Here, a simpler solver is used with two trailing edge parameters to reduce the computational cost so that a large number of evaluations is possible.) This corresponds to 50x50 evaluations of a two-dimensional design space (C_D at $C_L=0.71$, $M=0.74$) using a 2-D panel method. The two-dimensional design space describes the vertical movement of two B-spline poles adjacent to the trailing edge of an aerofoil. Computational noise often causes ridges in the design space, see also, for instance [9]. It is clear that gradient searches in this domain will not find the global optimum, but a local one, stopping at the bottom of a ridge. These problems are likely to be amplified in higher dimensional space. Inability to visualise high dimensional spaces can lead to an inability to fully exploit the additional flexibility.
- 20 Computational noise and expensive evaluation naturally leads to the use of response surface methodologies in design space optimisation.

Figure 10 shows the scatter plots for the 5-D military aircraft problem. In these, for instance, the quadratic nature of the relationship between C_L and C_D of every dependent and independent variable in the 5-D problem against every other variable can easily be identified. Additionally the independent variables show no relation with each other as should be expected given the DoE used to collect the data.

Figure 11 shows a set of SOM's for the 5-D military aircraft problem. To orient oneself with the SOM's it is necessary first to look at the picture of the glyphs shown top right. In this image, each of the glyphs is placed according to the value of α , θ and δ and are coloured according to the value of C_L . The SOM is a diagrammatic representation rather than a physical map of the design space, as illustrated by comparison between the SOM of C_L and the glyph image: the trends of the data are the same and have similar features. Consider the C_L SOM tile, it varies from red through green to purple across the diagonal. In the glyph image, the same variation can be seen from top left to bottom right. In the SOM's the diagonal trends of the maps of C_D , C_L , C_m , $trim$ and α show that they are all related (C_D , C_L , α monotonically and inversely to C_m and $trim$). The SOM's also show that the independent variables in the problem are unrelated, as they should be, given a suitable DoE. In higher dimensional problems, the SOM has been shown to indicate the first two principal components, as their SOM's can be related although in opposite directions (e.g. in opposite diagonal directions or vertically and horizontally). Bland regions in the SOM give an indication of rogue data (e.g. from unconverged CFD evaluations) and completely bland SOM's can help to identify unimportant variables.

Figure 10 and Figure 11 are not easy to interpret, and the next question is whether or not the type of visualisation presented in Figure 2 can be extended to higher dimensions to provide equally useful information. 200 CFD evaluations were used to obtain the Krig. Figure 12 shows a hierarchical axes technique (HAT) plot after [15] noting that filled squares denote optima located in the model using different optimisation methods. The other squares show the locations of evaluations in the final stages of simulated annealing of the response surface. The value of C_D is coloured within the tile. Colouring does not take place if the

inequality constraint on C_L is violated. The contour lines are contours of trim constraint. As shown in the Figure, within an individual tile camber and δ vary. As one goes from tile to tile in the horizontal direction of the main plot θ varies and in the vertical direction α varies. Then the top 81 tiles of this image represent the highest value of the fifth design variable, leading edge tip location. Each block of 81 tiles going down then represent lowering values of leading edge tip location. Only the top of this image is presented so that the smaller tiles are seen clearly. Two optima are shown: the first the result of a simulated annealing optimisation (red square) and the second the result of an exhaustive search in the representation data. This visualisation is similar in spirit to the triangles used in Figure 6 and [16], but with a less complex design space transformation. The HAT plot can however, only be used for data appreciation in up to 6 dimensions, as the tiles become too small thereafter. This picture is only possible because response surface methodologies enable the large amount of data required for plotting to be provided. The image gives confidence that the same optimum is being located in both cases and that the curve fit is well behaved.

Results from the RSM Kriging Process

To validate the RSM Kriging procedure some results from this process are given in Table 1. The variation in the results given in Table 1 could be cause for concern, except that reference to the visualisation shows that these results are close to each other and are therefore close to the same optimum. The CFD result is significantly different from the RSM, which means that there is mileage in building a new model, including this optimum and iterating until the optimum and CFD result obtained converge. The loading distribution and geometry of the final configuration are shown in Figure 14. In this case the loading distribution is nearly elliptic, as required, except for the compensation for wave drag in the outboard wing. The sweep is reduced compared to the initial configuration as large amounts of sweep give a large amount of downward pitching moment, which has been reduced. During a large number of optimisations of similar design spaces, in general there seem to be two optima in these design spaces. The second is an optimum in which the result is below the elliptic loading distribution at the root and above it at the tip. This has a deleterious effect on root

bending moment (*i.e.* increases it) and hence the structural optimum is worse and so in general the aerodynamics community chooses the answer presented here.

The GTM in the 5-D problem

5 Instead of Kriging the three design parameters of interest separately, in the SOM and GTM all the parameters of interest: the design variables, the objective and the constraints are transformed into the lower dimensional space $y(x, W)$. The thesis in which the GTM is developed [18] offers the visualisations posterior mean and mode projection, the responsibilities and the magnification
10 factors. This latter plot is a single image representing $y(x, W)$. However, instead the inventors use the individual components of the vector $y(x, W)$ pertaining to the variables of interest in the problem. From these components the penalty function can be obtained and plotted, with contours of C_L and *trim*, where $p(x)$ is given by:

$$15 \quad p(x) = C_D + |c_1 - 1.0| + \langle (C_{L_{total}} - C_L) / C_{L_{total}} \rangle,$$

Where $\langle \rangle$ are MacCauley brackets, in which the contents become zero if the function therein is negative, else the value of the function is used.

Figure 13 shows an image map representation of transformed data in 2-D latent design space $y(x, w)$ in accordance with an embodiment of the invention.
20 More particularly, this image map representation is provided by application of the GTM transformation for the 5-D aircraft design problem. Note that the penalty function is shown in the Figure, obtained from a combination of latent spaces for C_L , C_D and C_m , with contours of the latent spaces of C_L and *trim*. The cross marks the optimum, that is the point where C_D is the lowest and both C_L and *trim*
25 are satisfied. Here, a 60×60 latent space of 15×15 radial basis function (RBF) centres was used. Transformation back into real space gives the corresponding values of x_1 , x_2 , x_3 , x_4 and x_5 . These results are given in Table 2. The agreement between the CFD and GTM is excellent and the result is better than the preliminary result obtained using Kriging. Comparison between the GTM and
30 Kriging results is also shown in Figure 14. This Figure shows a loading distribution of optimised wing design using kriging and the 5-D inventive GTM in

accordance with an embodiment of the invention. Also shown are the starting and final CFD models. The GTM result is better as it is closer to an elliptic loading distribution. The new point could also now be used to build a new GTM, if desired, as the optimum could be used to build a new Krig model.

5 Use of the GTM for higher dimensional optimisation

The GTM was also used to optimise aerodynamic design spaces in 8 and 14 dimensions. In both cases a 60×60 latent space was used with 30×30 RBF centres. The visualisations are shown in Figure 15 and Figure 16 respectively. Note that Figure 15 is shown orientated in such a way to show similarity to the 14-D GTM shown in Figure 16. The solution to the 8-D problem is at $x_1 = 0.05058$, $x_2 = 0.01256$, $x_3 = 0.005531$, $x_4 = 0.00668$, $x_5 = 0.00953$, $x_6 = -0.00360$, $x_7 = 4.8462$, $x_8 = 1.7266$, with the GTM model after a number of iterations and the CFD solution being $C_L = 0.2022$, $C_D = 58.83$ counts, $C_m = -0.00359661$. This is probably reasonable compared to other optimisations, for instance a 3-D gradient search also gave $C_D = 58.8$ counts, with $C_L = 0.1994$ and $C_m = -0.02$ (higher C_L and lower C_m in this case), although there is probably more to come as the GTM solution is not on the boundary. This could possibly be found using a gradient search. The GTM in conjunction with an optimisation method does not seem to work as well in 14-D as in lower dimensions. It is probable that this is because the transformation is doing more *i.e.* going from 14-D to 2-D. To ameliorate this it should be possible for higher dimensions to transform to 4-D and view using the HAT plot discussed previously. The distinct similarities between Figure 15 and Figure 16 are evident and significant because they show that the same problem is being solved in both cases. It may assist in the future when trying to ascertain whether or not more limited sets of design variables can be used to adequately represent problems to compare the 2-D design spaces of both the lower and higher dimensional representations of the problem.

Other Potential Applications of the GTM in Design

During the kriging process it is possible to merge high and low fidelity data results. Plots of such data would show similarities and differences in the GTM.

Previous work has considered the use of the GTM in design space search, see [19]. However, here the SOM and GTM are used to predict how a low fidelity model relates to a high fidelity analysis. This inventive work does not consider the optimisation process per se in the lower dimensional representation. In [19] El-Beltagy indicates that the GTM algorithm can also be used as a visualisation tool to understand the discrepancies between the models and so reformulate the optimisation problem, although he does not show how.

Conclusions

A 2-dimensional plot generally provides the best data visualisation. Multiple dimension data needs to be transformed to lower dimensions to enable this. The HAT plot visualisation along with the RSM technology enables visualisation in up to 6 dimensions. The GTM has been shown to provide adequate visualisation and a quantitative graphical method for optimisation up to 14 dimensions. However, the step from 14-D to 2-D may be too large and therefore a 4-D GTM may be more accurate. More points in the 14D RBF and latent space may also improve the GTM.

Visualisation technology helps the designer to spend time inspecting results and ensuring correctness rather than dealing with large volumes of flow data. After a large number of numerical evaluations have been performed there is a need to identify any off trend results. The scatter plot method presented here is ideal for this purpose. The SOM also helps with this to give an overview. Response surface method technology eliminates inefficient design space sampling in the final stages of a gradient search optimisation. A balance is required between the number evaluations in the DoE, the number of cycles in the CFD, the number of points in the initial DoE and the number of further evaluations used. The trade-off between low-dimensional comprehension and high-dimensional accuracy impacts optimisation.

These type of visualisation methodologies are utilised to support design decisions such as the relative scaling of the design variables and constraints and choice of penalty function, which are important in optimisation. Also possible is the recognition of problems such as numerical noise and boundaries of

evaluation failure. Initial design of experiments can be improved in a systematic way by calculation of additional points dictated by maps of statistical and other error criteria. Significantly, the invention has utility for various aircraft design applications. Also, the invention can be embodied in software, if desired.

5 Although this technology has been developed with reference to aircraft aerodynamic design in particular, the design space visualisation and curve-fitting technology developed is general. It should therefore be equally applicable to other disciplines such as cost analysis, structures and computational electromagnetics, in which expensive analysis tools are used to find optima for

10 complicated design problems. It is expected to be particularly useful in multi-disciplinary design and situations where there are multiple optima in the design space.

Having thus described the present invention by reference to several preferred embodiments, it is to be appreciated that the embodiments are in all

15 respects exemplary and that modifications and variations are possible without departure from the spirit and scope of the invention. For example, whilst in the described embodiments the transformed data in the low-dimensional (2-D) image map representations are visually inspected, it is equally possible for the inspection to be performed computationally. It is to be also understood that the

20 described inventive transformation technique can be effectively applied to a wide range of high-dimensionality design spaces and that the transformation of data can be suitably performed into any one of a wide range of low-dimensionality design spaces.

It is to be also appreciated that whilst the GTM transformation technique is

25 applied in the described exemplary embodiments, it is equally possible to use alternative transformation techniques, SOM for example, instead of GTM, so as to realise the inventive technical effect.

References

- [1] H. P. Schwefel, *Evolution and Optimum Seeking*, Sixth Generation Computer Technology. John Wiley and Sons Inc., 1994, ISBN 0-471-57148-2.
- 5 [2] K. Madsen and O. Tingleff, "Robust subroutines for non-linear optimisation," Tech. Rep., Institute For Numerical Analysis, Technical University Of Denmark, February 1986.
- [3] M.D. McKay, R. J. Beckham and W. J. Conover, "A comparison of three methods for selecting values of input variables in the analysis of output from a computer code.," *Techometrics*, vol. 21, no. 2, pp. 239-245, 1979.
- 10 [4] R.B. Statnikov and J.B. Matusov. *MultiCriteria Optimisation and Engineering*. Chapman & Hall Publishers, ISBN 0-412-99231-0.
- [5] J. Sacks, W. J. Welch, T. J. Mitchell, and H. P. Wynn, "Design and analysis of computer experiments," *Statistical Science*, vol. 4, no. 4, pp. 409-435, 1989.
- 15 [6] D. Jones, M. Schonlau, and W. Welch, "Efficient global optimisation of expensive black-box functions," *Journal of Global Optimisation*, vol. 13, pp. 455-492, 1998.
- [7] D. R. Jones, "A taxonomy of global optimisation methods based on response surfaces," *Journal of Global Optimisation*, vol. 21, pp. 345-383, 2001.
- 20 [8] K. Morgan, J. Peraire and J. Peiro, "Unstructured grid methods for compressible flows", Special Course on Unstructured Grid Methods for Advection Dominated Flows, AGARD Report 787, March 1992.
- [9] V. Torczon, C. M. Siefert, and M. W. "Model-assisted pattern search." In *Proceedings: First International Workshop on Surrogate Modelling And Space Mapping for Engineering Optimisation*, held at the Technical University of
- 25 Denmark, November 16-18, 2000.
- [10] R. A. Bates, R. Fontana, C. Randazzo, E. Vaccarinao and H.P. Wynn, "Empirical Modelling Of Diesel Engine Performance for Robust Engineering Design" In: *Statistics for Engine Optimisation* pp.163-173, 1998.

[11] Inselberg and B. Dimsdale, "Parallel coordinates: A tool for visualising multi-dimensional geometry," in Proceedings, Visualisation 1990 IEEE CS Press Los Alamitos Calif., 1990, pp. 361-370.

[12] Goel, A., Baker, C., Shaffer, C., Grossman, B., Haftka, R., Mason, W.,
5 and Watson, L. (2000). VizCraft: A Problem Solving Environment for Configuration Design of a High Speed Civil Transport. Computing in Science and Engineering to appear. <http://citeseer.nj.nec.com/goel00vizcraft.html>

[13] T.Kohonen. Self -Organising Maps. Number {ISBN}: 3-540-67921-9. Springer-Verlag, 2000.

10 [14] P.C. Matthews, The Application of Self-Organising Maps in Conceptual Design, Ph.D. thesis, Fitzwilliam College, University of Cambridge, June 2001.

[15] T. Mihałalisin, J. Timlin, and J. Schwegler, "Visualising multivariate functions, data and distributions," in Readings in Information Visualisation: Using
15 Vision to Think, S. K. Card, J. Mackinlay, and B. Shneiderman, Editors., ISBN 1-55860-533-9, pp. 115-125. Morgan Kaufmann, 1999.

[16] B. Grossman, R. T. Haftka, W. H. Mason, L. T. Watson, C. Baker, S. Balabanov, S. Cox, A. Giunta, H. Kim, D. Knill, and D. Krasteva, "Effective use of surrogate models in aircraft design," Presentation at First International
20 Workshop on Surrogate Modelling and Space Mapping for Engineering Optimisation - held in Lyngby, Denmark, November 16-18th 2000.

[17] N.A.C. Cressie, "Statistics for Spatial Data", Revised Edition, Wiley-Interscience, ISBN-0-471-00255-0, 1993.

[18] M. Svensen, (1998) GTM: The Generative Topographic Mapping.
25 PhD Thesis, Aston University.

[19] M. A. El-Beltagy, (2000) "A Natural approach to Multilevel Optimisation in Engineering Design", PhD Thesis, University of Southampton.

[20] I. T. Nabney. "Algorithms for Pattern Recognition", ISBN1-85233-440-1. Springer, 2001.

Appendix 1 Kriging

Here, a Kriging approximation using a Gaussian kernel has been used to perform the RSM surface fits, see for instance in Sacks [5] or Jones [6,7]. If \mathbf{y} is an $(n \times 1)$ vector of responses evaluated at the locations \mathbf{x}_i , $i=1, \dots, n$, where n is the size of the DoE, then the response at the unsampled points \mathbf{x}^* is an estimate given by:

$$\hat{y}(\mathbf{x}^*) = \hat{\mu} + \mathbf{r}^T \mathbf{R}^{-1} (\mathbf{y} - \mathbf{1} \hat{\mu})$$

where:

$\mathbf{1}$ is the vector of ones and $\hat{\mu}$ is a weighted mean given by:

$$\hat{\mu} = \frac{\mathbf{1}^T \mathbf{R}^{-1} \mathbf{y}}{\mathbf{1}^T \mathbf{R}^{-1} \mathbf{1}}$$

with:

\mathbf{r} being a correlation vector based on the measured and estimated sample points, \mathbf{x}^* ,

\mathbf{R} is a matrix of correlation coefficients, based on the \mathbf{x}_i data points the $(i, j)^{th}$ entry of \mathbf{R} is given by $Corr[\mathbf{x}_i, \mathbf{x}_j]$ and the i^{th} element of \mathbf{r} by $Corr[\mathbf{x}_{n+1}, \mathbf{x}_i]$ with:

$$Corr[\mathbf{x}_i, \mathbf{x}_j] = \exp \left[- \sum_{h=1}^k 10^{\theta_h} \left| \mathbf{x}_{h,i} - \mathbf{x}_{h,j} \right|^{p_h} \right] \quad \theta_l > 0, l = 1, \dots, k,$$

for a sample of k variables at n points.

The hyperparameters θ_h , p_h and the factor on w_{min} in SVD (if used) are optimised by maximising the likelihood function or minimising:

$$(\sigma^2)^{\frac{n}{2}} |R|^{\frac{1}{2}}$$

Where the variance, $\hat{\sigma}^2$, is given by:

$$\hat{\sigma}^2 = \frac{(\mathbf{y} - \mathbf{1}\hat{\mu})^T \mathbf{R}^{-1} (\mathbf{y} - \mathbf{1}\hat{\mu})}{n}$$

Giving the mean square error of the predictor as:

$$s^2(\mathbf{x}^*) = \sigma^2 \left[1 - \mathbf{r}^T \mathbf{R}^{-1} \mathbf{r} + \frac{(\mathbf{1} - \mathbf{1}^T \mathbf{R}^{-1} \mathbf{r})^2}{\mathbf{1}^T \mathbf{R}^{-1} \mathbf{1}} \right]$$

Finally, the expected improvement is given by:

$$E[I(\mathbf{x}^*)] = \begin{cases} (y_{\min} - \hat{y}) \Phi\left(\frac{(y_{\min} - \hat{y})}{s}\right) + s \phi\left(\frac{(y_{\min} - \hat{y})}{s}\right) & \text{if the constraints are satisfied} \\ 0 & \text{else} \end{cases}$$

Here, y_{\min} is defined as the minimum of the input data, which satisfies the constraints. When considering minimisation, Expected Improvement can have its maximum value where the data is sparse or the approximation has a low value. The strategy is to resample where the Expected Improvement is maximised, then to form a new approximation and repeat.

Where the standard normal density and normal distribution functions are:

$$\phi(\mathbf{x}) = \frac{1}{\sqrt{2\pi}} e^{-\frac{x^2}{2}} \text{ and } \Phi(\mathbf{x}) = \int_{-\infty}^x \frac{1}{\sqrt{2\pi}} e^{-\frac{u^2}{2}} du$$

If the Euclidean norm is given by $\|\mathbf{z}\|$ the linear and thin plate spline radial basis functions are given as:

$$\text{Corr}[\mathbf{x}_i, \mathbf{x}_j] = \|\mathbf{z}\|$$

$$\text{Corr}[\mathbf{x}_i, \mathbf{x}_j] = \|\mathbf{z}\|^2 \log(\|\mathbf{z}\|)$$

These Equations do not provide kernels suitable for tuning or error analysis with statistical interpretation. It should be noted that alternative kriging algorithms are also widely used, which use the variogram instead of the correlation, see for example [17].

5 Appendix 2: Summary of the GTM algorithm

The GTM is a non-linear parametric mapping $y(x, \mathbf{W})$ from an L-dimensional latent space to a D dimensional data space, where normally, $L < D$, as illustrated in Figure 17. The sequence of steps for constructing a GTM model is given in [18] as:

- 10 Generate the grid of latent points: $\{\mathbf{x}_k\}$, $k = 1, \dots, K$.
- Generate the grid of basis function centres: $\{\mu_m\}$, $m = 1, \dots, M$.
- Select the basis function width σ .
- Compute the matrix of basis function activations, Φ .
- Initialise \mathbf{W} , randomly or using PCA.
- 15 Initialise β .
- If desired, select a value for α .
- Compute Δ , $\Delta_{kn} = \|\mathbf{t}_n - \Phi_k \mathbf{W}\|^2$.
- Repeat

Compute \mathbf{R} using Δ and β .

Compute \mathbf{G} using \mathbf{R} .

}

E-step

$\mathbf{W} = (\Phi^T \mathbf{G} \Phi + \lambda \mathbf{I})^{-1} \Phi^T \mathbf{R} \mathbf{T}$, where λ may be zero.

Compute Δ , $\Delta_{kn} = \|\mathbf{t}_n - \Phi_k \mathbf{W}\|^2$

Update β , using \mathbf{R} and Δ .

}

M-step
- 20 Until convergence

- 24 -

The squared distances required to update β in the M-step gets 'reused' when calculating the responsibilities in the following E-step. In our case we use the implementation of this formulation by Ian Nabley of Aston University in Netlab, [20].

CLAIMS

1. A method of transforming data from a high-dimensional design space and deriving an optimum value for a predetermined function representative of the transformed data in the low-dimensional design space, which derivation is further effected in the low-dimensional design space in dependence upon an inspection of the transformed data.
5
2. A method of transforming data from a high-dimensional to low-dimensional design space, and deriving a conditional value for a predetermined function representative of the transformed data in the low-dimensional design space, which derivation is further effected in the low-dimensional design space in dependence upon an inspection of the transformed data.
10
3. A method as claimed in claim 1 or 2 wherein the value is derived by (a) establishing a mathematical combination of a number of independent design variables and dependent design variables relating to the function, and (b) modifying said combination in the low-dimensional design space to derive therefrom the desired value for the function at which various constraints associated with the function are satisfied and at which the function has a conditional high or low value in relation to other possible values of the function which are determined in accordance with the modification of said combination.
15
20
4. A method as claimed in claim 1, 2 or claim 3 wherein said transformation into the low-dimensional design space is performed by application of a Generative Topographic Map (GTM) technique.
5. A method as claimed in any preceding claim, comprising the step of transforming data from a first high-dimensional design space and from a second, different high-dimensional design space into a low-dimensional design space, comparing the different transformed data sets in said low-dimensional design space and identifying therefrom similarities between the different transformed data sets to indicate a correspondence between the first and second high-dimensional design spaces.
25
30

6. A method as claimed in claim 5 wherein the first high-dimensional design space is a 5-dimensional design space, the second high-dimensional design space is an 8-dimensional design space, the third is a 14-dimensional design space, and the low-dimensional design space is a two-dimensional design space.
7. A method as claimed in any of claims 3 to 6 wherein the data transformation into the low-dimensional design space is performed in a manner which takes account of the effect of each of the design variables relating to the function.
8. A method as claimed in any preceding claim wherein the value derivation is effected by generating an image map representation of the transformed data in the low-dimensional design space, and visually identifying an intersecting region in the image map representation, which intersecting region provides an indication of said value.
9. A method as claimed in any preceding claim for application to an aircraft design or to an aerodynamic surface design.
10. A method substantially as herein described with reference to the accompanying drawings.
11. A program element comprising program code operable to carry out a method as claimed in any preceding claim.
12. The program element of claim 11 on a carrier medium.
13. A data processing system for transforming data from a high-dimensional to low-dimensional design space adapted and arranged to carry out a method as claimed in any preceding claim.
14. A data processing system substantially as herein described with reference to the accompanying drawings.

ABSTRACT OF THE DISCLOSURE
DESIGN BY SPACE TRANSFORMATION
FROM HIGH TO LOW DIMENSIONS

5 A method is provided for transforming data from a high-dimensional to low-dimensional design space, and for inspecting the transformed data in such a manner as to permit effective navigation and exploration of the high-dimensional design space. Conveniently, an optimum/conditional value for a prescribed functional representation of the transformed data can be derived by visual inspection of a 2-D image map representation of the transformed data.

10 Significantly, the invention has utility for various aircraft design applications and although this technology has been developed with reference to aircraft aerodynamic design in particular, the design space visualisation and curve-fitting technology developed is general. It should therefore be equally applicable to other disciplines such as cost analysis, structures and
15 computational electromagnetics, in which expensive analysis tools are used to find optima for complicated design problems. It is expected to be particularly useful in multi-disciplinary design and situations where there are multiple optima in the design space.

Figure 13

1/19
FIGURE 1




Figure 1

2/19
FIGURE 2




Figure 2

3/19
FIGURE 3




Figure 3

4/19
FIGURE 4




Figure 4

5/19
FIGURE 5




Figure 5

6/19
FIGURE 6




Figure 6

7119
FIGURE 7




Figure 7

8/19
FIGURE 8




Figure 8

10/19
FIGURE 10




Figure 10

11/19
FIGURE 11




Figure 11

12/19
FIGURE 12




Figure 12

13 / 19
TABLE 1

Method	x_1	x_2	x_3	x_4	x_5	c_1	C_L	C_D
Simulated annealing on response surfaces	3.583	5.1936	1.1835	0.0156	10.2366	1.0000	0.1993	68.07e-04
Additional CFD evaluation	3.583	5.1936	1.1835	0.0156	10.2366	1.0004	0.2035	86.31e-04

Table 1

14/19
TABLE 2

Method	x_1	x_2	x_3	x_4	x_5	trim	C_L	C_D
5D GTM	2.7877	4.0083	0.5342	0.0506	10.1614	0.9803	0.1966	0.0064
Additional CFD evaluation	2.7877	4.0083	0.5342	0.0506	10.1614	0.9920	0.1934	0.0054

Table 2

15 / 19

FIGURE 13




Figure 13

16/19
FIGURE 14





Figure 14

17/19
FIGURE 15




Figure 15

18/19

FIGURE 16



Figure 16

19/19

FIGURE 17




Figure 17

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.